INDEPENDENT

BATTERY CERTIFICATE

AVILOO
BATTERY DIAGNOSTICS

CERTIFICATE NUMBER: A011ED1E-258E-466C-9D50-F51F7F5D67C9

VEHICLE

BRAND: Kia
MODEL: Niro EV - 64,8 kWh

MILEAGE: 31,869 mi
VIN: KNDCR3L12P5037539
DATE AND TIME:
9/3/26, 9:21 AM

EXECUTED BY: Reds Auto and Truck

RESULTS

Independent
STATE OF HEALTH (SOH)


97.4 %

ENERGY 63kWh | 65kWh

WLTP RANGE 278mi | 286mi

RATING

BENCHMARKING
How does your vehicle compare to comparable vehicles?



CHECKS

- Battery Management System (BMS) ✓
- Battery Sensor ✓
- Battery Measurements ✓
- Battery Cell Voltages ✓
- Vehicle Communication ✓

SCAN FOR DETAILS

EVALUATION

EXCELLENT HEALTH - NO ABNORMALITIES DETECTED

Based on the detailed battery diagnostics performed with the AVILOO FLASH Test, we hereby certify that the drive battery of this vehicle is in excellent condition.

The drive battery is therefore officially AVILOO Certified.

Dr. Marcus Berger, CEO

AVILOO CERTIFIED
THIS BATTERY IS TESTED AND AVILOO CERTIFIED

ENERGY

	Gross	Net (Nominal)	Usable
Current:	66.2kWh	63.1kWh	60.5kWh
New:	68.0kWh	64.8kWh	62.2kWh

RANGE

	WLTP	Typical	Individual
Current:	278mi	212mi	249mi
New:	286mi	218mi	256mi

EXECUTION PROTOCOL

AVILOO Box connected. **09:21:55**

- FLASH Test started. ✓
- Data acquisition started. ✓
- Vehicle detected. ✓
- Data acquisition completed. ✓
- Data analysis started. ✓
- Data analysis completed. ✓

SENSORS

Voltage Sensor	✓
Current Sensor	✓
Temperature Sensors	✓
Cell Voltage Sensors	✓

BMS


	Value	Status
BMS State of Charge (SoC)*:	39%	
SoC calculation accuracy:		✓
BMS State of Health (SoH)*:	100%	
SoH calculation accuracy:		✓

MEASUREMENTS

	Min	Max	Delta	Status
Battery Temperature	68.0F	71.6F	3.6F	✓
Cell Voltage	3.660V	3.660V	0mV	✓
Pack Voltage	351.8V			
Average Current	-1.2A			

CELL VOLTAGES DIAGRAM

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
1 - 20	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660
21 - 40	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660
41 - 60	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660
61 - 80	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660
81 - 96	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660	3.660				



*The values shown here were read directly from the vehicle's battery management system (BMS) and are calculated and provided by the vehicle manufacturer. The State of Health (SoH) displayed corresponds to the value reported by the BMS and is CARA-certified.

DISCLAIMER: The test result includes the currently calculated state of health (SoH) of the drive battery. The determination is based on data provided by the vehicle. These are evaluated by AVILOO's algorithms using statistical and analytical models. Manipulation of the data in the control unit leads to an incorrect result. The indicated SoH has a technically induced fluctuation range (deviation) of no more than 3% in at least 95% of reference measurements. It should be noted that this tolerance applies to the SoH determination at the cell level and not to the SoH of the entire battery. This is because the state of charge of individual cells may vary, which can negatively affect the current SoH of the battery. However, this can be compensated by the Battery Management System (BMS) or during a calibration. The result reflects the condition of the battery at the time of the test. No conclusions can be drawn about the future state of health of the battery from this. Statements about mechanical damage or external influences are not part of this diagnosis.

AVILOO Inc. | 4949 S Syracuse St Ste 550 | 80237 Denver, CO | United States | help.usa@aviloo.com

A011ED1E-258E-466C-9D50-F51F7F5D67C9