

INDEPENDENT BATTERY CERTIFICATE



CERTIFICATE NUMBER: 702BEAA5-CE85-4B8E-92BE-F79F8F9EA82F

VEHICLE

BRAND: Chevrolet

MODEL: Equinox EV - 85 kWh

MILEAGE: 22,141 mi

VIN: 3GN7DLRR5RS270697

DATE AND TIME:

9/24/26, 8:47 AM

EXECUTED BY: Reds Auto and Truck

RESULTS

Independent

STATE OF HEALTH (SOH)

98.4 %

ENERGY

88kWh | 90kWh




WLTP RANGE

228mi | 232mi

RATING

BENCHMARKING

How does your vehicle compare to comparable vehicles?



CHECKS

Battery Management System (BMS)



Battery Sensor



Battery Measurements



Battery Cell Voltages



Vehicle Communication



SCAN FOR DETAILS

EVALUATION

GOOD HEALTH - NO ABNORMALITIES DETECTED

Based on the detailed battery diagnostics performed with the AVILOO FLASH Test, we hereby certify that the drive battery of this vehicle is in good condition.


The drive battery is therefore officially AVILOO Certified.

Marcus Berger

Dr. Marcus Berger, CEO



CELL VOLTAGES DIAGRAM



EXECUTION PROTOCOL

AVILOO Box connected.	08:47:20
FLASH Test started.	✓
Vehicle detected.	✓
Data acquisition started.	✓
Data acquisition completed.	✓
Data analysis started.	✓
Data analysis completed.	✓

RANGE

	WLTP	Typical
Current:	219-228mi	169mi
New:	223-232mi	171mi

ENERGY

	Gross	Net (Nominal)	Usable
Current:	91.0kWh	88.3kWh	86.5kWh
New:	92.5kWh	89.7kWh	87.9kWh

MEASUREMENTS

	Min	Max	Delta	Status
Battery Temperature	66.2F	68.0F	1.8F	✓
Cell Voltage	3.606V	3.610V	4mV	✓
Pack Voltage	288.7V			
Average Current	-1.4A			

BMS

	Value	Status
BMS State of Charge (SoC)*:	31%	
SoC calculation accuracy:		✓
BMS State of Health (SoH)*:	100%	
SoH calculation accuracy:		✓

SENSORS

Voltage Sensor	✓
Current Sensor	✓
Temperature Sensors	✓
Cell Voltage Sensors	✓

*The values shown here were read directly from the vehicle's battery management system (BMS) and are calculated and provided by the vehicle manufacturer. The State of Health (SoH) displayed corresponds to the value reported by the BMS and is CARA-certified.

DISCLAIMER: The test result includes the currently calculated state of health (SoH) of the drive battery. The determination is based on data provided by the vehicle. These are evaluated by AVILOO's algorithms using statistical and analytical models. Manipulation of the data in the control unit leads to an incorrect result. The indicated SoH has a technically induced fluctuation range (deviation) of no more than 3% in at least 95% of reference measurements. It should be noted that this tolerance applies to the SoH determination at the cell level and not to the SoH of the entire battery. This is because the state of charge of individual cells may vary, which can negatively affect the current SoH of the battery. However, this can be compensated by the Battery Management System (BMS) or during a calibration. The result reflects the condition of the battery at the time of the test. No conclusions can be drawn about the future state of health of the battery from this. Statements about mechanical damage or external influences are not part of this diagnosis.