INDEPENDENT

BATTERY CERTIFICATE

AVILOO
BATTERY DIAGNOSTICS

CERTIFICATE NUMBER: 2C872F5C-3735-4510-94F3-887B5D8BA903

VEHICLE

BRAND: Cadillac
MODEL: Lyriq - 107,6 kWh

MILEAGE: 29,348 mi
VIN: 1GYKPMRK5RZ138846
DATE AND TIME:
10/21/26, 9:20 AM

EXECUTED BY: 712 Auto Sales

RESULTS

Independent
STATE OF HEALTH (SOH)


96.6 %

ENERGY 104kWh | 108kWh

WLTP RANGE 368mi | 381mi

RATING

BENCHMARKING
How does your vehicle compare to comparable vehicles?



below average | average | above average

CHECKS

- Battery Management System (BMS) ✓
- Battery Sensor ✓
- Battery Measurements ✓
- Battery Cell Voltages ✓
- Vehicle Communication ✓

SCAN FOR DETAILS

EVALUATION

EXCELLENT HEALTH - NO ABNORMALITIES DETECTED

Based on the detailed battery diagnostics performed with the AVILOO FLASH Test, we hereby certify that the drive battery of this vehicle is in excellent condition.

The drive battery is therefore officially AVILOO Certified.

Dr. Marcus Berger, CEO

AVILOO CERTIFIED
THIS BATTERY IS TESTED AND AVILOO CERTIFIED

EXECUTED BY:

712 AUTO SALES

ENERGY

	Gross	Net (Nominal)	Usable
Current:	107.2kWh	103.9kWh	101.8kWh
New:	111.0kWh	107.6kWh	105.4kWh

RANGE

	WLTP	Typical
Current:	360-368mi	274mi
New:	372-381mi	284mi

EXECUTION PROTOCOL

AVILOO Box connected.	09:20:38
FLASH Test started.	✓
Data acquisition started.	✓
Vehicle detected.	✓
Data acquisition completed.	✓
Data analysis started.	✓
Data analysis completed.	✓

SENSORS

Voltage Sensor	✓
Current Sensor	✓
Temperature Sensors	✓
Cell Voltage Sensors	✓

BMS

	Value	Status
BMS State of Charge (SoC)*:	54%	
SoC calculation accuracy:		✓
BMS State of Health (SoH)*:	97%	
SoH calculation accuracy:		✓

MEASUREMENTS

	Min	Max	Delta	Status
Battery Temperature	60.8F	62.6F	1.8F	✓
Cell Voltage	3.774V	3.779V	5mV	✓
Pack Voltage	362.6V			
Average Current	-0.9A			

*The values shown here were read directly from the vehicle's battery management system (BMS) and are calculated and provided by the vehicle manufacturer. The State of Health (SoH) displayed corresponds to the value reported by the BMS and is CARA-certified.

DISCLAIMER: The test result includes the currently calculated state of health (SoH) of the drive battery. The determination is based on data provided by the vehicle. These are evaluated by AVILOO's algorithms using statistical and analytical models. Manipulation of the data in the control unit leads to an incorrect result. The indicated SoH has a technically induced fluctuation range (deviation) of no more than 3% in at least 95% of reference measurements. It should be noted that this tolerance applies to the SoH determination at the cell level and not to the SoH of the entire battery. This is because the state of charge of individual cells may vary, which can negatively affect the current SoH of the battery. However, this can be compensated by the Battery Management System (BMS) or during a calibration. The result reflects the condition of the battery at the time of the test. No conclusions can be drawn about the future state of health of the battery from this. Statements about mechanical damage or external influences are not part of this diagnosis.

AVILOO Inc. | 4949 S Syracuse St Ste 550 | 80237 Denver, CO | United States | help.usa@aviloo.com

2C872F5C-3735-4510-94F3-887B5D8BA903