INDEPENDENT

BATTERY CERTIFICATE

AVILOO
BATTERY DIAGNOSTICS

CERTIFICATE NUMBER: 45DFA35C-4E89-4A3B-9C0A-8B79072B52AB

VEHICLE

BRAND: Polestar
MODEL: 2 - 82 kWh

MILEAGE: 17,775 mi
VIN: YSMFE3KAXRL231281
DATE AND TIME:
11/4/26, 2:59 PM

EXECUTED BY: 712 Auto Sales

RESULTS

Independent
STATE OF HEALTH (SOH)

99.4 %

ENERGY 79kWh | 80kWh

WLTP RANGE 404mi | 406mi

RATING

BENCHMARKING
How does your vehicle compare to comparable vehicles?



below average | average | above average

CHECKS

- Battery Management System (BMS) ✓
- Battery Sensor ✓
- Battery Measurements ✓
- Battery Cell Voltages ✓
- Vehicle Communication ✓

SCAN FOR DETAILS

EVALUATION

EXCELLENT HEALTH - NO ABNORMALITIES DETECTED

Based on the detailed battery diagnostics performed with the AVILOO FLASH Test, we hereby certify that the drive battery of this vehicle is in excellent condition.

The drive battery is therefore officially AVILOO Certified.

Marcus Berger

Dr. Marcus Berger, CEO

AVILOO CERTIFIED
BATTERY IS TESTED AND AVILOO CERTIFIED

EXECUTED BY:

712 AUTO SALES

ENERGY

	Gross	Net (Nominal)	Usable
Current:	81.5kWh	79.5kWh	77.5kWh
New:	82.0kWh	80.0kWh	78.0kWh

RANGE

	WLTP	Typical	Individual
Current:	351-404mi	297mi	264mi
New:	353-406mi	299mi	265mi

EXECUTION PROTOCOL

AVILOO Box connected. **14:59:53**

- FLASH Test started. ✓
- Data acquisition started. ✓
- Vehicle detected. ✓
- Data acquisition completed. ✓
- Data analysis started. ✓
- Data analysis completed. ✓

SENSORS

- Voltage Sensor ✓
- Current Sensor ✓
- Temperature Sensors ✓
- Cell Voltage Sensors ✓

BMS

	Value	Status
BMS State of Charge (SoC)*:	60%	
SoC calculation accuracy:		✓
BMS State of Health (SoH)*:	100%	
SoH calculation accuracy:		✓

MEASUREMENTS

	Min	Max	Delta	Status
Battery Temperature	61.9F	64.2F	2.3F	✓
Cell Voltage	3.912V	3.925V	12mV	✓
Pack Voltage	423.4V			
Average Current	-0.9A			

CELL VOLTAGES DIAGRAM

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
1 - 20	3.923	3.918	3.920	3.919	3.924	3.921	3.919	3.923	3.922	3.922	3.915	3.917	3.919	3.921	3.919	3.923	3.921	3.921	3.920	3.920
21 - 40	3.920	3.916	3.921	3.921	3.922	3.921	3.920	3.921	3.923	3.918	3.921	3.919	3.923	3.919	3.923	3.922	3.921	3.922	3.923	3.923
41 - 60	3.922	3.919	3.921	3.919	3.919	3.921	3.922	3.918	3.923	3.922	3.921	3.918	3.922	3.925	3.921	3.921	3.920	3.919	3.919	3.921
61 - 80	3.923	3.920	3.920	3.922	3.920	3.924	3.921	3.923	3.919	3.919	3.921	3.921	3.914	3.912	3.916	3.920	3.923	3.924	3.921	3.923
81 - 100	3.923	3.920	3.921	3.923	3.918	3.923	3.923	3.921	3.924	3.919	3.920	3.922	3.919	3.920	3.921	3.919	3.921	3.923	3.921	3.923
101 - 108	3.922	3.923	3.921	3.923	3.923	3.915	3.917	3.922												



*The values shown here were read directly from the vehicle's battery management system (BMS) and are calculated and provided by the vehicle manufacturer. The State of Health (SoH) displayed corresponds to the value reported by the BMS and is CARA-certified.

DISCLAIMER: The test result includes the currently calculated state of health (SoH) of the drive battery. The determination is based on data provided by the vehicle. These are evaluated by AVILOO's algorithms using statistical and analytical models. Manipulation of the data in the control unit leads to an incorrect result. The indicated SoH has a technically induced fluctuation range (deviation) of no more than 3% in at least 95% of reference measurements. It should be noted that this tolerance applies to the SoH determination at the cell level and not to the SoH of the entire battery. This is because the state of charge of individual cells may vary, which can negatively affect the current SoH of the battery. However, this can be compensated by the Battery Management System (BMS) or during a calibration. The result reflects the condition of the battery at the time of the test. No conclusions can be drawn about the future state of health of the battery from this. Statements about mechanical damage or external influences are not part of this diagnosis.

45DFA35C-4E89-4A3B-9C0A-8B79072B52AB